

Power Bank 2000 + RV Port



THE POWER BANK 2000

Power your devices anytime, anywhere with portable, long-lasting battery storage that's perfect for home, camping, road trips, festivals, emergencies and more.



HOME BACKUP POWER SOLUTION

Our most dynamic off-grid solution to backup power, charges 99% of household and on-the-go devices.



3 WAYS TO RECHARGE

Standard AC Charging, Solar Charging, Car Charging, Hybrid Charging (Multiple charging types can be used simultaneously.)



OPTIMIZED BATTERY RETENTION

Can retain up to 80% of capacity up to 3,500 complete charge cycles.



8,064WH EXPANDABLE CAPACITY

Add up to two (2) 3000W Project Solar Expansion Packs, and up to six (6) 200W Project Solar Portable Solar Panels.



15 OUTPUT PORTS

(4) Standard AC Outputs, (1) 110-120V RV Port, (4) USB-A Outputs, (2) USB-C Outputs, (2) DC 5525 Outputs, (1) Cigar Port, (1) 15W Wireless Charger



GRADE-A LITHIUM IRON PHOSPHATE

Lose less than 1% capacity p/ year with reliable, long- lasting battery life, stability, safety, and high discharge rate.



WEATHER PROTECTION

The Power Bank features a durable, flame-retardant exterior, with a removable water-resistant cover and TPU-protected ports.



12 MONTH WARRANTY

We guarantee your satisfaction with a 30-day money-back policy and a 12-month warranty, ensuring that you receive a quality product free from defects.





Power Bank 2000 + RV Port

CAPACITY:	1920 Wh (expandable up to 8064 Wh) (25.6V, 75Ah)
RATED POWER:	2000W
PEAK/SURGE POWER:	4000W
DEPTH OF DISCHARGE (DOD):	90%
BATTERY LIFE:	Can retain up to 80% of capacity at 3,500 complete charge cycles
BATTERY CHEMISTRY:	Lithium Iron Phosphate
WARRANTY:	1 Year
WEIGHT:	48.5 lbs
DIMENSIONS:	16.1in x 10in x 11.6in
CHARGING TEMPERATURE RANGE:	0°C ~ 45°C / 32°F ~ 113°F
DISCHARGING TEMPERATURE RANGE:	-20°C ~ 45°C / -4°F ~ 113°F
CHARGING TYPES:	Standard AC Charging, Solar Charging, Car Charging (multiple charging types can be used simultaneously)
DC INPUT PORT GX16MF:	2
DC INPUT PORT 5521:	1
AC OUTPUTS:	5
USB-A OUTPUTS:	4
USB-C OUTPUTS:	2
DC 5525 OUTPUTS:	2
CIGAR PORT:	1
WIRELESS CHARGER:	1
MAXIMUM SOLAR INPUT:	1200W